



Glosten

2019 | FRENCH
AMERICAN
INNOVATION
DAY
BOSTON

ENGINEERED TO OPTIMIZE THE
COMMERCIAL COST OF ENERGY FOR DEEP
WATER ENERGY

PELASTAR FLOATING WIND TURBINE

PROPRIETARY INFORMATION

PELASTAR – AN OPTIMIZED WIND FARM SOLUTION



Reduce capital and O&M costs to develop the lowest LCOE Floating Offshore Wind Turbine Farm:

- **Minimize floating foundation hull steel weight.**
- **Minimize hydrodynamic response and mooring loads.**
- **Maximize turbine availability.**
- **Provide robust foundation and mooring for severe weather.**
- **Optimize cost for commercial scale operations (not a single demonstrator).**

A tension leg platform (TLP) meets these requirements.

TENSION LEG PLATFORM TECHNOLOGY HISTORY



SeaStar TLP installed in 1998

Originates from deep water oil & gas technology in the 1980s.

- Suited for water depths greater than 1,000 ft.
- Allows onshore assembly.
- Lower mass than other floating solutions.
- No active ballast required.
- Stiff mooring results in reduced response to waves.
- Higher turbine efficiency
- Reduced dynamic loading on turbine components


PELASTAR TENSION LEG PLATFORM OVERVIEW

Project History:


- 2009 – Carbon Trust Award
- 2011 – DOE Funding
- 2012 – ETI FEED-level Design

Project Highlights:

- Supports a 6 MW turbine.
- DNV-GL approved Basis of Design and FEED-level design.
- 1:50 scale model test performed with software validation and reviewed by DNV-GL.



- Tower
- Interface Flange
- Transition Piece
- Access Platform
- Upper Column
- 5 Arms
- Lower Hull
- Export Cable
- Tendons
- Anchors



PELASTAR INNOVATIVE TECHNOLOGY

- **Centralized buoyancy type TLP minimizes wave loads and therefore mooring loads.**
- **5-arm design reduces cost from previous 6-tendon designs.**
- **5-arm design provides redundancy to survive loss of one tendon.**
- **5-arm design distributes and lowers peak tendon loads during a hydrodynamic slack event.**
- **Synthetic tendon design is cost-effective and robust.**



MOORING TECHNOLOGY INNOVATION

Synthetic Tendon Development


- Developed with DSM and FibreMax.
- High strength to survive slack-line events in extreme weather conditions.
- Cables allow initial creep and then set to minimize life-cycle tendon length adjustments.



Moored Response Motions


- Tank testing validates significantly reduced angular response motions.

TLP WIND FARM MOORING BENEFITS



Traditional Catenary Mooring

- Extensive footprint.
- Significant seabed impact.
- Catenary mooring requires significant chain lengths.
- Interference between mooring and power grid.



TLP Vertical Tendon Mooring

- Compact footprint.
- Minimal impact on seabed.
- Minimal impact on fishing ops.
- Efficient power grid connection.

OFFSHORE INSTALLATION CONCEPT

- **Existing offshore dynamic position (DP) crane vessels.**
 - Turbine and TLP foundation loaded on vessel for transit to site.
 - Crane lifts TLP foundation on site.
 - Foundation ballasted and tendons connected.
 - Foundation de-ballasted and tendon tensions verified.
 - Crane hook releases from foundation.
 - Crane lifts turbine onto foundation and secured.
- **Allows onshore assembly of TLP tower and turbine.**
- **Allows onshore commissioning of turbine.**



SCALABLE SOLUTION



	6 MW	12 MW
Water Depth (LAT)	55 m	100 m
Rotor Diameter	150 m	220 m
Hub Height (above LAT)	108 m	137 m
Tower Weight	450 mt	1,350 mt



Glostén

Kyle Beattie, PE
kcbeattie@glosten.com
New Bedford, MA
Seattle, WA



Rocket Landing Vessel




Emergency Vessel Towing System



Olmsted Dam Heavy Lift Barge



Oakland Bay Bridge Demolition



Ice Capable Research Vessel



Foiling Passenger Vessel

PROPRIETARY INFORMATION